

Pressalit Calmo 556

Designer


Design year

Toilet seat with soft close incl. hinge in stainless steel. Optional lift -off function.

Pressalit

2007

Features	Soft close	
Item number	556000-BZ5999 EAN:5708590274188	
	Say goodbye to slamming seats. And welcome to Calmo - the calm luxury in everyday life. A seat with minimalistic and pure lines where soft close is taken for granted.	
Colour	White	
Description	PRESSALIT toilet seat with cover, model "Calmo", art. no. 556 made of colour ingrained duroplast with D72/BZ5/D02/D15 hinge of stainless steel dismounting of seat/cover makes cleaning easier - centre distance: D02/D15/D72: 133 - 215 mm, BZ5: 155 mm - load - ring seat 240 kg - suitable for universal toilets - 10 year guarantee	
	436 — 220 — 288 — A7171 — A7050 — A7050	A4001
Design type	Wrap-over	





Pressalit Calmo 556

Toilet seat with soft close incl. hinge in stainless steel. Optional lift -off function.

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Maximum load Load - ring seat 240 kg

Weight (kg) 3,062

Carton size 494x390x72 mm

Gross weight (kg) 3,392

Colli size 504x400x366 mm

Colli weight (kg) 16,96

Qty per colli 5

Colli per pallet 18

Qty per pallet 90

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.

Warranty

Pressalit provides a 10-year product warranty on your toilet seat. Pressalit will repair or exchange the toilet seat for the same or another useable model, at Pressalit's discretion, in the event of a material or manufacturing defect in your toilet seat appearing within 10 years of the date of purchase with normal use. This product warranty is conditional upon

proof of purchase of the toilet seat.

Subject to changes in the product range, technical changes and printing errors.





Pressalit Calmo 556
Toilet seat with soft close incl. hinge in stainless steel. Optional lift -off function.





www.pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com

