

BILATERAL LOADING CONTAINER

2SIDE SYSTEM 3600


3600 L
Capacity


1440 Kg
Load


1180 mm
Opening height



TECHNICAL SPECIFICATIONS









BILATERAL LOADING CONTAINER

2SIDE SYSTEM 3600

FEATURES

- Manufactured by rotational moulding with high-density linear polyethylene, mass-coloured and stabilised against the combined action of water and UV rays.
- Recyclable and environmentally friendly materials are used in their production.
- The pigments used do not contain heavy materials.
- The body is provided with ribs for strength and resistance. Exclusive CONTENUR design.
- Versions for each type of collection: paper, glass, packaging and organic.
- Recyclability rate: 100%...
- Treatment of the components by white zinc plating.

CERTIFICATIONS

- This product has the following official certifications:
 - -EN 13071-1 European Standard.
 - -170001 Universal Accessibility Standard.
 - -Ecodesign Certificate, UNE-EN ISO 14006 standard.

EQUIPMENT AND ACCESSORIES

- Lifting system: double hook or Kinshofer.
- Circular loading opening at a height of 1180 mm.
- Corrosion-protected metal lifting-emptying system.
- Large personalisation space with maximum dimensions of 1145 x 480 mm (upper area) and 580 x 215 mm (lower area).
- Overlapping bottom gates to prevent spillage and to store leachate (compliance with EN 13071, 2% capacity).









BILATERAL LOADING CONTAINER

2SIDE SYSTEM 3600

CUSTOMISATION AND EQUIPMENT

Possibility of customising the container with different accessories to offer solutions adapted to every need: lid opening pedal, hinged lid, manual lock, customisation.



PEDAL



MANUAL LOCK



LENGTHWISE AND CROSSWISE POSITIONING



LIFTING SYSTEMS Double hook Kinshofer



TELESCOPIC ROD





CUSTOMISATION Upper area: 1145 x 480 mm Lower area: 580 x 215 mm



OPENINGS ON BOTH SIDES



OVERLAPPING GATES



LID OPTIONS Hinged lid Rectangular opening 900x200 mm Two openings Ø200 mm Two openings Ø300 mm