



Ref.: 24985

USE

For small renovations and light works

For OCASIONAL cut of floor stoneware and FRECUENT cut of wall tiles.

FUNCTIONAL CHARACTERISTICS

Multipoint breaker in aluminium.

CLOSED sliders (no slider bearings) and aluminium tool holder.

Embossed steel plate base with central rib.

Guides supports made of injected aluminium. **STURDIER.**

Double guide, better **VISIBILITY** of the scoring line.

Milimetrical square made of ABS.

Solid, chromed steel guides of $\varnothing 16$ mm with anti-corrosion treatment.

Lateral stop made of steel plate for repetitive cut with 45° template.

Interchangeable scoring wheels to get the maximum **PERFORMANCE** and cut **QUALITY**. Compatible with $\varnothing 6$ to 10 mm wheels.

$\varnothing 6$ mm scoring wheel included.

www.rubi.com



TECHNICAL SPECIFICATIONS

- Cutting length: 61 cm.
- Maximum tile size in diagonal: 43x43 cm.
- Maximum thickness: 10 mm.
- Weight: 4.985 kg.

PACKAGING

1 unit carton box full-coloured.

Unitary box dimensions: 767x148x92 mm.

1 unit gross weight: 5.415 kg.

Sales unit: 6 units (bulk box).

Bulk box dimensions: 785x315x310 mm.

Bulk box weight: 32.490 kg.

Units per pallet: 72 units (12 bulk boxes).

Pallet weight: 411 kg.

www.rubi.com