



Ref.: 24984

USE

For small renovations and light works

For OCASIONAL cut of floor stoneware and FRECUENT cut of wall tiles.

FUNCTIONAL CHARACTERISTICS

Multipoint breaker in aluminium.

CLOSED sliders (no slider bearings) and aluminium tool holder.

Embossed steel plate base with central rib.

Guides supports made of injected aluminium. STURDIER.

Double guide, better VISIBILITY of the scoring line.

Milimetrical square made of ABS.

Hollow, chromed steel guides of $\varnothing 16$ mm with anti-corrosion treatment.

Lateral stop made of steel plate for repetitive cut with 45° template.

Interchangeable scoring wheels to get the maximum PERFORMANCE and cut QUALITY. Compatible with $\varnothing 6$ to 10 mm wheels.

$\varnothing 6$ mm scoring wheel included.

www.rubi.com



TECHNICAL SPECIFICATIONS

- Cutting length: 51 cm.
- Maximum tile size in diagonal: 36x36 cm.
- Maximum thickness: 10 mm.
- Weight: 2.980 kg.

PACKAGING

1 unit carton box full-coloured.

Unitary box dimensions: 667x148x92 mm.

1 unit gross weight: 3.365 kg.

Sales unit: 6 units (bulk box).

Bulk box dimensions: 685x315x310 mm.

Bulk box weight: 20.190 kg.

Units per pallet: 72 units (12 bulk boxes).

Pallet weight: 283 kg.

www.rubi.com