



USE

- For dry drilling ceramic materials; wall tiles, glazed stoneware, porcelain stoneware and natural stone.

FUNCTIONAL CHARACTERISTICS

- SUPERPRO quality.
- Vacuum brazed diamond bit.
- For use with grinder.
- M14 thread connection for the global market and 5/8" thread connection for the US market.
- Dry cutting.
- Maximum working speed: 14,000 r.p.m.
- Maximum working thickness: 36 mm.
- Air cooling, by orbital movement.
- Those up to 12 mm in diameter incorporate a wax plug to improve the initial lubrication of the bit (first 4 - 5 perforations).
- For the US market, an adapter is offered to change the M14 thread to the 5/8" thread (ref. 05987).

- References available for global market:

Reference	Diameter	Rpm max.	Maximum drilling thickness
05988	6 mm	14000	36 mm
05989	8 mm	14000	36 mm
05990	10 mm	14000	36 mm
05991	12 mm	14000	36 mm
04910	20 mm	14000	36 mm
57903	25 mm	14000	36 mm
04911	28 mm	14000	36 mm
04912	35 mm	14000	36 mm
04913	43 mm	14000	36 mm
04914	50 mm	14000	36 mm
04915	60 mm	14000	36 mm
04916	65 mm	14000	36 mm
04917	68 mm	14000	36 mm
05992	75 mm	14000	36 mm
57904	80 mm	14000	36 mm
57906	85 mm	14000	36 mm
57907	100 mm	14000	36 mm
57908	120 mm	14000	36 mm

- References available for the US market:

Reference	Diameter	Rpm max.	Maximum drilling thickness
5993	1/4" (6 mm)	14000	36 mm
5932	5/16" (8 mm)	14000	36 mm
5901	3/8" (10 mm)	14000	36 mm
5934	25/32" (20 mm)	14000	36 mm
5902	1-1/8" (28 mm)	14000	36 mm
5936	1-11/16" (43 mm)	14000	36 mm
5903	2" (50 mm)	14000	36 mm
5937	2-9/16" (65 mm)	14000	36 mm
5938	2-61/64" (75 mm)	14000	36 mm

PACKAGING

- Cylindrical transparent PVC blister with process label.
- Dimensions:
 - o Ø 6 a 28 mm: 3.4x3.4x12.5 cm.
 - o Ø 35 mm: 4,3x4,3x12,8 cm.
 - o Ø 43 mm: 5,2x5,2x13,1 cm.
 - o Ø 50 a 65 mm: 7,4x7,4x13,6 cm.
 - o Ø 68 a 75 mm: 8.5x8.5x14 cm.
 - o Ø 80 a 120 mm: 13.8x13.8x8.6 cm.
- 1 unit per blister.
- Warning for ref. 05988/05989/05990/05991 and for 05993/05932/05901: Store at temperatures below 80°C.