



Ref.: 25940

*Version with
transport case

Ref.: 26958

USE

Versatile electric mixer.

For cementitious adhesives, resins, paints and other materials.

FUNCTIONAL CHARACTERISTICS

Bimaterial double handle grip. Improved ERGONOMICS, COMFORT and STABILITY.

With 2 speed gearbox.

Progressive switch (R.P.M. regulation) to OPTIMIZE the mixing of each material.

SAFETY locking switch. Avoids involuntary triggering.

Interchangeable mixing paddle with M14 thread connection. Greater VERSATILITY.

Double insulation.

LIGHT and RESISTANT. High RELIABILITY.

Direct access to brushes housing.

Include $\varnothing 120$ mm. mixing paddle for cementitious adhesives.

Available version with transport case.

www.rubi.com



TECHNICAL SPECIFICATIONS

- Power: 1200W.
- Voltages: 210-240V/50-60Hz (ref. 25940) (ref. 26958 with case).
 - 110-130V/50-60Hz UK (ref. 25942).
 - 210-240V/50-60Hz UK (ref. 25944) (ref. 26904 with case).
 - 110-130V/50-60Hz USA. (ref. 25948).
 - 210-240V/50-60Hz AUS (ref. 24954).
- Ø Maximum mixing paddle: 140 mm.
- R.P.M.:
 - V1: 0 – 650 r.p.m.
 - V2: 0 – 850 r.p.m.
- Weight: 5.5 Kg (Version with case: 7.8 Kg).

PACKAGING

Full colour carton box. (Version with case: Full colour carton sleeve).

Unitary box dimensions: 37x32x24 cm. (Version with case: 42x31x26 cm.)

Unitary box weight: 6.5 Kg. (Version with case: 8.5 Kg.)

Sales unit: 2 units. Bulk box with RUBI flexography.

Bulk box dimensions: 66x40x26 cm. (Version with case: 67x45x29 cm.)

Bulk box weight: 13 Kg. (Version with case: 17.1 Kg.)

Units per pallet: 24 (Version with case: 18 units)

Pallet dimensions: 120x80x93 cm. (Version with case a: 120x100x100 cm.)

Pallet weight: 174 Kg. (Version with case: 171 Kg.)

NORM

Meets de following standards:

EN 60745-1, EN ISO 12100, EN 55014-1, EN 55014-2, EN 61000-3-2, EN 61000-3-3, EN 62321.

Conforms to the essential requirements of the directives:

2006/42/EC, 2014/30/EC, 2012/19/EC, 2011/65/EC.

www.rubi.com