



M-120 FI 3H PADDLE

VERSION:

R-V.1.02

DATE:

NOV2016



Ref.: 76942



USE

For mortars and cementitious adhesives.

FUNCTIONAL CHARACTERISTICS

Three-blade helix for a performance 15% higher compared with an equivalent two-blade helix.

Less effort while mixing. Improves electric mixer long-lasting.

Vibration reduction. Easier use.

The material rises through the inner section of the mixing paddle and falls on the outside. This motion allows for a homogeneous mixture of viscous materials such as mortar, cement, tile adhesive, etc.

Made of steel with black cataphoresis finish.

Tool-less FAST-IN connection.

Adaptable, with FAST-IN adapter (ref. 76907), to all RUBIMIX* and other mixers.

*Except RUBIMIX-9 DUPLEX and RUBIMIX-50-N

www.rubi.com



M-120 FI 3H PADDLE

VERSION:

R-V.1.02

DATE:

NOV2016

TECHNICAL SPECIFICATIONS

Mixture capacity: 15-25 kg.

Paddle height: 600 mm.

Helix diameter: 120 mm.

Mixer minimum power: 950 W.

Weight: 1,08 kg.

PACKAGING

One-piece packaging: Full-color PVC band with rubber hooker.

One-piece packaging dimensions: 64.5x12x12 cm.

Sales unit: 2 units. Bulk box with RUBI flexography.

Bulk box dimensions: 66.5x13x13.5 cm.

Bulk box weight: 2.5 Kg.

www.rubi.com