



M-140 R 3H PADDLE

VERSION:

R-V.1.01

DATE:

DEC2016

Ref.: 76919



USE

For mortars and cementitious adhesives.

FUNCTIONAL CHARACTERISTICS

Three-blade helix for a performance 15% higher compared with an equivalent two-blade helix.

Less effort while mixing. Improves electric mixer long-lasting.

Vibration reduction. Easier use.

The material rises through the inner section of the mixing paddle and falls on the outside. This motion allows for a homogeneous mixture of viscous materials such as mortar, cement, tile adhesive, etc.

Made of steel with black cataphoresis finish.

M14 Thread connection.

Adaptable to all RUBIMIX* and other mixers.

*Except RUBIMIX-9 DUPLEX and RUBIMIX-50-N

www.rubi.com



M-140 R 3H PADDLE

VERSION:

R-V.1.01

DATE:

DEC2016

TECHNICAL SPECIFICATIONS

Mixture capacity: 25-40 kg.

Paddle height: 600 mm.

Helix diameter: 140 mm.

Mixer minimum power: 1200 W.

www.rubi.com

It is the customer's responsibility to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice