



USE

For cutting bricks, non-reinforced concrete, terrazzo and a great variety of masonry materials.

High performance and speed of cut.

Dry cut.

DIAMOND BLADE CHARACTERISTICS

Sintered TURBO blade.

Laser welding.

For GRINDERS use.

NOT RECOMMENDED for mitre cut.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

PRO quality.

Rim height: 7 mm.

Inner diameter: 22.2 mm

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 25917 – Ø115 PRO: Rim thickness: 2 mm.

Maximum RPM: 13,300.

Ref. 31980 – Ø125 PRO: Rim thickness: 2.2 mm.

Maximum RPM: 12,250.

Ref. 25918 – Ø230 PRO: Rim thickness: 2.5 mm.

Maximum RPM: 6,650.

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 25917 – Ø115: 17.5x15 mm.

Ref. 31980 – Ø125: 17.5x15 mm.

Ref. 25918 – Ø230: 30x26 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com