



USE

For cutting all kind of ceramic tiles.

High quality of cut.

For materials <25 mm thick.

Dry cut.

DIAMOND BLADE CHARACTERISTICS

Sintered CONTINUOUS RIM blade.

Laser welding.

For GRINDERS use.

NOT RECOMMENDED for mitre cut.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height: 7 mm.

Inner diameter: 22.2 mm

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 30882 – Ø115: Rim thickness: 1.6 mm.

Maximum RPM: 13,300.

Ref. 30883 – Ø125: Rim thickness: 1.6 mm.

Maximum RPM: 12,250.

Ref. 30888 – Ø230: Rim thickness: 1.9 mm.

Maximum RPM: 6,650.

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 30882 – Ø115: 17.5x15 mm.

Ref. 30883 – Ø125: 17.5x15 mm.

Ref. 30888 – Ø230: 30x26 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com