



USE

For the cut of porcelain tiles.

High speed of cut.

Dry cut.

DIAMOND BLADE CHARACTERISTICS

Sintered TURBO blade.

Laser welding.

Depressed ring for steel body reinforcement.

For GRINDERS and HANDHELD SAW use.

NOT RECOMMENDED for mitre cut.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPER PRO quality.

Rim height: 7 mm.

Inner diameter: 22.2 mm

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 31972 – Ø115: Rim thickness: 1.4 mm.

Maximum RPM: 13,300.

Ref. 31973 – Ø125: Rim thickness: 1.4 mm.

Maximum RPM: 12,250.

Ref. 31975 – Ø180: Rim thickness: 1.6 mm.

Maximum RPM: 8,500.

Ref. 31978 – Ø230: Rim thickness: 1.6 mm.

Maximum RPM: 6,650.

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 31972 – Ø115: 17.5x15 mm.

Ref. 31973 – Ø125: 17.5x15 mm.

Ref. 31975 – Ø180: 24.5x21 mm.

Ref. 31978 – Ø230: 30x26 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com