



USE

For the cut of porcelain tiles.

Greater performance.

For materials <25 mm thick.

Dry cut.

DIAMOND BLADE CHARACTERISTICS

Sintered J-SLOT blade.

Laser welding.

Extra flanges welded (point weld) on steel body for reinforcement.

Eliminates tensions when cutting.

For GRINDERS use.

NOT RECOMMENDED for mitre cut.

Warning:

DUE TO THE INCREASE OF THICKNESS OF THE BODY ON THE REINFORCED AREA, THE CUT LINE COULD BE MOVED FROM THE GUIDING SYSTEMS OF THE CHOSEN TOOLS.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPER PRO quality.

Rim height: 7 mm.

Inner diameter: 22.2 mm

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 32932 – Ø115: Rim thickness: 1.4 mm.

Maximum RPM: 13,300.

Ref. 32933 – Ø125: Rim thickness: 1.4 mm.

Maximum RPM: 12,250.

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 32932 – Ø115: 17.5x15 mm.

Ref. 32933 – Ø125: 17.5x15 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com