



USE

For cutting abrasive materials such bricks, calcareous terrazzo or marble.

High speed of cut.

Perfect for materials >25 mm thick.

Dry cut.

DIAMOND BLADE CHARACTERISTICS

Sintered SEGMENTED blade.

Laser welding.

For GRINDERS use.

NOT RECOMMENDED for mitre cut.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height: 7 mm.

Inner diameter: 22.2 mm

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 32902 – Ø115: Rim thickness: 2.2 mm.

Maximum RPM: 13,300.

Ref. 32903 – Ø125: Rim thickness: 2.2 mm.

Maximum RPM: 12,250.

Ref. 32908 – Ø230: Rim thickness: 2.6 mm.

Maximum RPM: 6,650.

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 32902 – Ø115: 17.5x15 mm.

Ref. 32903 – Ø125: 17.5x15 mm.

Ref. 32908 – Ø230: 30x26 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com