



USE

For cutting bricks, non-reinforced concrete, terrazzo and a great variety of masonry materials.

High speed of cut.

Perfect for materials >25 mm thick.

Wet cut.

DIAMOND BLADE CHARACTERISTICS

Sintered SEGMENTED blade.

Laser welding.

Suitable for use in wet tile and masonry saws that incorporate a protection system in accordance with standard for the use of segmented blades.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

PRO quality.

Rim height: 10 mm.

Inner diameter: 25.4 mm

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 32974 - Ø250: Rim thickness: 2.6 mm.

Maximum RPM: 6,150.

Ref. 32972 - Ø300: Rim thickness: 2.6 mm.

Maximum RPM: 5,100.

Ref. 32973 - Ø350: Rim thickness: 3 mm.

Maximum RPM: 4,400.

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 32974 - Ø250: 30x26 mm.

Ref. 32972 - Ø300: 36x31 mm.

Ref. 32973 - Ø350: 42x36 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com