



USE

For cutting all kind of ceramic tiles.

High quality of cut.

For materials <25 mm thick.

Wet cut.

DIAMOND BLADE CHARACTERISTICS

Sintered CONTINUOUS RIM blade.

Laser welding.

For TILE SAWS use.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height: 7 mm. ($\varnothing 300/350 - 10$ mm.)

Inner diameter: $\varnothing 115/125 - 22.2$ mm.

$\varnothing 180/230/ - 22.2-25.4$ mm. (reduction ring included)

$\varnothing 200/250/300/350 - 25.4$ mm.

Rim thickness: $\varnothing 115/125/180/200 - 1.7$ mm.

$\varnothing 230 - 2$ mm.

$\varnothing 250/300 - 2.2$ mm.

$\varnothing 350 - 2.6$ mm.

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 30942 - $\varnothing 115$: Maximum RPM: 13,300

Ref. 30943 - $\varnothing 125$: Maximum RPM: 12,250

Ref. 30945 - $\varnothing 180$: Maximum RPM: 8,500

Ref. 30946 - $\varnothing 200$: Maximum RPM: 7,650

Ref. 30948 - $\varnothing 230$: Maximum RPM: 6,650

Ref. 30949 - $\varnothing 250$: Maximum RPM: 6,150

Ref. 30950 - $\varnothing 300$: Maximum RPM: 5,100

Ref. 30951 - $\varnothing 350$: Maximum RPM: 4,400

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 30942/30943 - $\varnothing 115/125$: 17.5x15 mm.

Ref. 30945/30946 - $\varnothing 180/200$: 24.5x21 mm.

Ref. 30948/30949 - $\varnothing 230/250$: 30x26 mm.

Ref. 25935 - $\varnothing 300$: 36x31 mm.

Ref. 32971 - $\varnothing 350$: 42x36 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com