



USE

For cutting hard materials such granite, slate, quartz composites, rustic tiles, clinker and porcelain tiles.

High quality of cut.

For materials <25 mm thick.

Wet cut.

DIAMOND BLADE CHARACTERISTICS

Sintered CONTINUOUS RIM blade.

Laser welding.

For TILE SAWS use.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height: 7 mm. ($\varnothing$ 300/350 – 10 mm.)

Inner diameter: $\varnothing$ 125/180/230 – 22.2 mm.

$\varnothing$ 200/250/300/350 – 25.4 mm.

Rim thickness: $\varnothing$ 125/180/200 – 1.7 mm.

$\varnothing$ 230 – 2 mm.

$\varnothing$ 250/300 – 2.2 mm.

$\varnothing$ 350 – 2.6 mm.

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 30923 - $\varnothing$ 125: Maximum RPM: 12,250

Ref. 30925 - $\varnothing$ 180: Maximum RPM: 8,500

Ref. 30926 - $\varnothing$ 200: Maximum RPM: 7,650

Ref. 30928 - $\varnothing$ 230: Maximum RPM: 6,650

Ref. 30929 - $\varnothing$ 250: Maximum RPM: 6,150

Ref. 30930 - $\varnothing$ 300: Maximum RPM: 5,100

Ref. 30931 - $\varnothing$ 350: Maximum RPM: 4,400

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 30923 – $\varnothing$ 125: 17.5x15 mm.

Ref. 30925/30926 - $\varnothing$ 180/200: 24.5x21 mm.

Ref. 30928/30929 - $\varnothing$ 230/250: 30x26 mm.

Ref. 30930 - $\varnothing$ 300: 36x31 mm.

Ref. 30931 - $\varnothing$ 350: 42x36 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com