



## USE

For the cut of hard materials such granite, slate, quartz composites, rustic tiles, clinker and porcelain tiles.

High speed of cut.

Wet cut.

## DIAMOND BLADE CHARACTERISTICS

Sintered TURBO VIPER blade.

Laser welding.

Welded flange for steel body reinforcement.

NOT RECOMMENDED for mitre cut.

Suitable for use in wet tile and masonry saws that incorporate a protection system in accordance with standard for the use of segmented blades.

### **Warning:**

***DUE TO THE INCREASE OF THICKNESS OF THE BODY ON THE REINFORCED AREA, THE CUT LINE COULD BE MOVED FROM THE GUIDING SYSTEMS OF THE CHOSEN TOOLS.***

[www.rubi.com](http://www.rubi.com)



## COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height: 10 mm.

Inner diameter: 25.4 mm

Maximum perimeter speed: 80 m/s.

## OWN TECHNICAL SPECIFICATIONS

Ref. 31936 – Ø200: Rim thickness: 1.6 mm.

Maximum RPM: 7,650.

Ref. 31937 - Ø250: Rim thickness: 1.6 mm.

Maximum RPM: 6,150.

Ref. 31938 – Ø300: Rim thickness: 2 mm.

Maximum RPM: 5,100.

Ref. 31939 – Ø350: Rim thickness: 2.4 mm.

Maximum RPM: 4,400.

## PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 31936 – Ø200: 24.5x21 mm.

Ref. 31937 – Ø250: 30x26 mm.

Ref. 31938 – Ø300: 36x31 mm.

Ref. 31939 – Ø350: 42x36 mm.

Sales unit: 1 blister.

## NORM

Conform to EN-13236.

[www.rubi.com](http://www.rubi.com)