



## USE

For cutting abrasive materials such bricks, calcareous terrazzo or marble.

High performance and speed of cut.

Wet cut.

## DIAMOND BLADE CHARACTERISTICS

Sintered TURBO blade.

Laser welding.

Suitable for use in wet tile and masonry saws that incorporate a protection system in accordance with standard for the use of segmented blades.

[www.rubi.com](http://www.rubi.com)



## COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height: 7.5 mm.

Inner diameter: 25.4 mm

Maximum perimeter speed: 80 m/s.

## OWN TECHNICAL SPECIFICATIONS

Ref. 31906 – Ø200 SUPERPRO: Rim thickness: 2.5 mm.

Maximum RPM: 7,650.

Ref. 31909 – Ø250 SUPERPRO: Rim thickness: 2.5 mm.

Maximum RPM: 6,150.

Ref. 31910 – Ø300 SUPERPRO: Rim thickness: 3 mm.

Maximum RPM: 5,100.

## PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 31906 - Ø200: 24.5x21 mm.

Ref. 31909 - Ø250: 30x26 mm.

Ref. 31910 - Ø300: 36x31 mm.

Sales unit: 1 blister.

## NORM

Conform to EN-13236.