



USE

For grinding and polishing of natural stone, composites and concrete surfaces.

Dry use.

PADS' CHARACTERISTICS

Flexibles resin pads with VELCRO fastening.

Complete grading range for each work:

#50 y 100 for beginning works, when it needs a big size grain.

#200, 400 y 800 for medium grinding works.

#1500 y 3000 are the finest grain and suitable for a finishing polishing works.

Finally, to complete the polishing pad range, RUBI incorporate its polisher pad (BUFF), necessary for polishing works on natural Stone and cured concrete. Main use on white and light colour surfaces. When polishing dark colour surfaces to test that colour is not affected is recommended.

RECOMMENDED use with adjustable speed grinder.

Half rigid support with M14 thread is needed (Ref. 62986)..

Easy to use.

www.rubi.com



TECHNICAL SPECIFICATIONS

Diameter: Ø100 mm.

Maximum RPM: 3,000.

Net weight: 19 gr.

PACKAGING

Blister with full-colour carton insert.

Blister dimensions: 175x155x50 mm.

Gross weight: 50 gr.

Sales unit: 1 blister.



Ref. 62970



Ref. 62971



Ref. 62972



Ref. 62973



Ref. 62974



Ref. 62975



Ref. 62976



Ref. 62977

www.rubi.com