



Ref.: 66940

## USE

Electric scraper.

To remove cement base grouts.

Ideal for repair jobs (substitution of broken tiles) and renovations.

## FUNCTIONAL CHARACTERISTICS

ERGONOMIC design and bi-material finishes, for a better COMFORT and greater STABILITY.

Equipped with 3 speeds.

QUICK Lock/Unlock system for an EASY blade replacement.

Double insulation.

LIGHT and RESISTANT. High RELIABILITY.

Tungsten carbide blades. RE-SHARPENABLES for a greater performance.

Includes blades for 1.5 mm (ref. 66810, use only on speed 1) and 3 mm (ref. 66812) grouts.

Includes 2 special blades (steel made) to remove rests of thin-set from the back of the tiles or on the substrate.

With transport case.

[www.rubi.com](http://www.rubi.com)



## TECHNICAL SPECIFICATIONS

- Power: 250W.
- Voltages: 230V/50Hz (ref. 66940).  
230V/50Hz UK. (ref. 66941).  
120V/60Hz USA. (ref. 66942).
- Cadence: S1: 6500 b.p.m. / S2: 8000 b.p.m. / S3: 9500 b.p.m.
- Impact energy: 0.5 J.
- Weight: 1.3 kg (electric scraper only).
- Stroke length: 2 mm.
- Protection class: II – Double insulation.
- Power level/acoustic pressure (LWA)+: 90 Db(A) / K= 3 Db(A).
- Vibrations: < 2,52 m/s<sup>2</sup> / K= 1,5 m/s<sup>2</sup>.

## PACKAGING

Full colour carton box.

Unitary box dimensions: 33.2x10.7x25.5 cm.

Unitary box weight: 2.48 Kg.

Unit sales: 1 unit.

## REGULATIONS

Meets de following standards:

EN 60745-1, EN ISO 12100, EN 55014-1, EN 55014-2, EN 61000-3-2, EN 61000-3-3.

Conforms to the essential requirements of the directives:

2006/42/CE, 2004/108/CE, 2012/19/CE, 2011/65/EC.

[www.rubi.com](http://www.rubi.com)