



## USE

To check horizontals, verticals and 45° levels.

## FUNCTIONAL CHARACTERISTICS

SHOCKPROOF and SOLID epoxy locked vials.

UV resistant.

Measurements in NORMAL position: horizontal, vertical and 45°.

MAQCHINED surface up to measures of 120 cm.

SHOCK-ABSORBING end caps made in rubber.

REMOVABLE end caps to mark into corners and narrow edges.

## TECHNICAL SPECIFICATIONS

- Made in aluminium profile: 20x50x1.8 mm.
- Accuracy: 0.5 mm/m.
- Weight:

Ref. 76920 - RUBILEVEL 40: 255 gr.

Ref. 76921 - RUBILEVEL 50: 306 gr.

Ref. 76922 - RUBILEVEL 60: 353 gr.

Ref. 76923 - RUBILEVEL 80: 455 gr.

Ref. 76924 - RUBILEVEL 100: 550 gr.

Ref. 76925 - RUBILEVEL 120: 656 gr.

Ref. 76926 - RUBILEVEL 150: 851 gr.

Ref. 76927 - RUBILEVEL 200: 1.176 gr.

[www.rubi.com](http://www.rubi.com)



## PACKAGING

Screen-printed characteristics pictograms and brand on aluminium body.

Unitary packaging with transparent film.

Sales unit: 8 units/box. Bulk box with RUBI flexography (except 150 and 200 models with only 2 units par box).

Bulk boxes dimensions:

RUBILEVEL 40: 40.5x9.5x10.5 cm.

RUBILEVEL 50: 50.5x9.5x10.5 cm.

RUBILEVEL 60: 60.5x9.5x10.5 cm.

RUBILEVEL 80: 80.5x9.5x10.5 cm.

RUBILEVEL 100: 100.5x9.5x10.5 cm.

RUBILEVEL 120: 120.5x9.5x10.5 cm.

RUBILEVEL 150: 150.5x5.25x5.5 cm.

RUBILEVEL 200: 200.5x5.25x5.5 cm.

Bulk boxes weight:

RUBILEVEL 40: 2.1 Kg.

RUBILEVEL 50: 2.5 Kg.

RUBILEVEL 60: 3 Kg.

RUBILEVEL 80: 3.8 Kg.

RUBILEVEL 100: 4.5 Kg.

RUBILEVEL 120: 5.4 Kg.

RUBILEVEL 150: 1.8 Kg.

RUBILEVEL 200: 2.5 Kg.

[www.rubi.com](http://www.rubi.com)