



## USE

To check horizontals, verticals and 45° levels.

## FUNCTIONAL CHARACTERISTICS

SHOCKPROOF and SOLID epoxy locked vials.

UV resistant.

Measurements in NORMAL position: horizontal, vertical and 45°.

MILLED surface.

SHOCK-ABSORBING end caps made in rubber.

REMOVABLE end caps to mark into corners and narrow edges.

Rare earths MAGNETS.

## TECHNICAL SPECIFICATIONS

- Made in aluminium profile: 20x50x1.8 mm.
- Accuracy: 0.5 mm/m.
- Weight:

Ref. 76928 - RUBILEVEL MAGNET 40: 281 gr.

Ref. 76929 - RUBILEVEL MAGNET 50: 333 gr.

Ref. 76930 - RUBILEVEL MAGNET 60: 381 gr.

Ref. 76931 - RUBILEVEL MAGNET 80: 492 gr.

[www.rubi.com](http://www.rubi.com)



## PACKAGING

Screen-printed characteristics pictograms and brand on aluminium body.

Unitary packaging with transparent film.

Sales unit: 8 units/box. Bulk box with RUBI.

Bulk boxes dimensions:

RUBILEVEL MAGNET 40: 40.5x9.5x10.5 cm.

RUBILEVEL MAGNET 50: 50.5x9.5x10.5 cm.

RUBILEVEL MAGNET 60: 60.5x9.5x10.5 cm.

RUBILEVEL MAGNET 80: 80.5x9.5x10.5 cm.

Bulk boxes weight:

RUBILEVEL MAGNET 40: 2.4 Kg.

RUBILEVEL MAGNET 50: 2.8 Kg.

RUBILEVEL MAGNET 60: 3.2 Kg.

RUBILEVEL MAGNET 80: 4.1 Kg.

[www.rubi.com](http://www.rubi.com)