RUBILEVEL ANTISHOCK

VERSION: R-V.1.01

DATE: FEB2016

USE

To check horizontal, vertical and 45° levels.

FUNCTIONAL CHARACTERISTICS

SHOCKPROOF and SOLID epoxy locked vials.
UV resistant.
MAGNIFIED horizontal vial for the CLEAREST view of the bubble.
Measurements in NORMAL position: horizontal, vertical and 45°. Also from TOP surface.
DUAL view vertical vial for front measurements. Eliminates parallax error.
Two finely MILLED surfaces.
Lower Surface with V-Groove for pipe measurements.
ERGONOMIC bi-material handle for a comfortable grip.
SHOCK-ABSORBING end caps made in rubber.
REMOVABLE end caps to mark into corners and narrow edges.

TECHNICAL SPECIFICATIONS

- Made in reinforced aluminium profile: 30x66x2 mm.
- Accuracy: 0.5 mm/m.
- Weight:

Ref. 76932 - RUBILEVEL ANTISHOCK 60: 644 gr.
Ref. 76933 - RUBILEVEL ANTISHOCK 80: 813 gr.
Ref. 76934 - RUBILEVEL ANTISHOCK 100: 984 gr.
Ref. 76935 - RUBILEVEL ANTISHOCK 120: 1.161 gr.

GERMANS BOADA S.A. Pol. Can Rosés, Avda. Olimpiades 89-91, 08191 RUBI (Barcelona) SPAIN • Telf: +34 936 80 65 00 • gboada@rubi.com • www.rubi.com

www.rubi.com

Is the customer's responsibility to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.

PACKAGING

Screen-printed characteristics pictograms and brand on aluminium body.
Unitary packaging with transparent film.
Sales unit: 8 units/box. Bulk box with RUBI flexography.
Bulk boxes dimensions:

RUBILEVEL ANTISHOCK 60: 60.5x13.5x14 cm.
RUBILEVEL ANTISHOCK 80: 80.5x13.5x14 cm.
RUBILEVEL ANTISHOCK 102: 100.5x13.5x14 cm.
RUBILEVEL ANTISHOCK 120: 120.5x13.5x14 cm.

Bulk boxes weight:

RUBILEVEL ANTISHOCK 60: 5.3 Kg.
RUBILEVEL ANTISHOCK 80: 6.7 Kg.
RUBILEVEL ANTISHOCK 100: 8 Kg.
RUBILEVEL ANTISHOCK 120: 9.5 Kg.

GERMANS BOADA S.A. Pol. Can Rosés, Avda. Olimpiades 89-91, 08191 RUBI (Barcelona) SPAIN • Telf: +34 936 80 65 00 • gboada@rubi.com • www.rubi.com

Is the customer's responsibility to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.