



USE

To check horizontal, vertical and 45° levels.
Ideal for tile setting and layout and general masonry Jobs.

FUNCTIONAL CHARACTERISTICS

SHOCKPROOF and SOLID epoxy locked vials.

UV resistant.

Measurements in NORMAL position: horizontal and vertical.

DUAL view vertical vial for front measurements. Eliminates parallax error.

MILLED Surface.

SHOCK ABSORBING rubber "anvils".

TECHNICAL SPECIFICATIONS

- Made in T shaped cast aluminium profile: 20x46 mm.
- Accuracy: 0.5 mm/m.
- Weight:

Ref. 76936 - RUBILEVEL ALUCAST 40: 350 gr.

Ref. 76937 - RUBILEVEL ALUCAST 50: 390 gr.

Ref. 76938 - RUBILEVEL ALUCAST 60: 460 gr.

Ref. 76939 - RUBILEVEL ALUCAST 80: 620 gr.

www.rubi.com



PACKAGING

Adhesive label with characteristics pictograms and brand on aluminium body.

Unitary packaging with transparent film.

Sales unit: 8 units/box. Bulk box with RUBI flexography.

Bulk boxes dimensions:

RUBILEVEL ALUCAST 40: 40.5x10x5 cm.

RUBILEVEL ALUCAST 50: 50.5x10x5 cm.

RUBILEVEL ALUCAST 60: 60.5x10x5 cm.

RUBILEVEL ALUCAST 80: 80.5x10x5 cm.

Bulk boxes weight:

RUBILEVEL ALUCAST 40: 3 Kg.

RUBILEVEL ALUCAST 50: 3.3 Kg.

RUBILEVEL ALUCAST 60: 3.9 Kg.

RUBILEVEL ALUCAST 80: 5.2 Kg.

www.rubi.com