USE

For brick-type installation of ceramic tiles.

FUNCTIONAL CHARACTERISTICS

GUARANTEE a perfect grout and constant alignment.

Widths available: 1, 1.5, 2, 3, 5, 7 and 10 mm.

Two types (according to measures):

• Solid (1, 1.5, 2 and 3 mm): Specially recommended when installing tiles on walls. Greater stiffness against crushing and deformation.

• Hollow (5, 7 and 10 mm): Its grid structure guarantees its dimensional regularity. It also allows the filling of the T at the time of applying the grout mortar, avoiding future malformations or movements in the grout.

The 1, 1.5 and 2 mm models have a longer arm length in order to offer a better support in the LARGE FORMAT of ceramics tiles.

GERMANS BOADA S.A. Pol. Can Roses, Avda. Olimpiades 89-91, 08191 RUBI (Barcelona) SPAIN • Telf.: +34 936 80 65 00 • gboada@rubi.com • www.rubi.com

It is the customer's responsibility to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.

TECHNICAL SPECIFICATIONS

Made of Polypropylene (PP).

Dimensions:

- Long arm length: 30 mm (1, 1.5, 2, 3 and 5 mm models).
  44 mm (7 mm model).
  48.5 mm (10 mm model).
- Short arm length: 15 mm (1, 1.5, 2, 3 and 5 mm models).
  25.5 mm (7 mm model).
  29 mm (10 mm model).
- Height: 3.5 mm (1, 1.5, 2 and 3 mm models).
  6.5 mm (5 mm model).
  7.5 mm (7 mm model).
  9.5 mm (10 mm model).

PACKAGING

Polyethylene (PET) bag in full-color and heat-sealed.
Units per bag: 1 mm. 300 u. (Ref. 02859).
1.5 mm. 300 u. (Ref. 02860).
2 mm. 300 u. (Ref. 02861).
3 mm. 200 u. (Ref. 02923).
5 mm. – 100 u. (Ref. 02924).
7 mm. – 100 u. (Ref. 02925).
10 mm. – 50 u. (Ref. 02926).
Sales unit: 10 bags.

Available bags of large volume: 1 mm. - 1000 u. (Ref. 02862).
1.5 mm. - 1000 u. (Ref. 02863).
2 mm. - 1000 u. (Ref. 02864).
3 mm. - 1000 u. (Ref. 02063).
5 mm. - 1000 u. (Ref. 02064).
10 mm. - 500 u. (Ref. 02395).
Sales unit (large volume): 1 bag.

GERMANS BOADA S.A. Pol. Can Roses, Avda. Olimpiades 89-91, 08191 RUBI (Barcelona) SPAIN • Telf.: +34 936 80 65 00 • gboada@rubi.com • www.rubi.com

www.rubi.com

It is the customer's responsibility to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.