



Ref.: 17909

Ref.: 17910 (INCH. VERSION).

USE

Professional manual cutter, with high-performance MULTIPPOINT breaker.

For INTENSIVE cutting of all types of ceramic tile, ideal for porcelain tiles (Bia/Ala) and extruded tiles (Alb/Alia).

FUNCTIONAL CHARACTERISTICS

Ø30 mm tubular steel guides with 2 mm wall thickness.

Head wit, extra-long aluminium sliders, with “self-lubricated” friction bearings.

Aluminium mobile breaker, equipped with plastic protector to AVOID marks on SMOOTH surfaces.

Breaker’s lock system, by ratchet mechanism, and unlocking system, by trigger, allows scoring and breaking with one hand only. Higher SPEED of use. Increases PERFORMANCE in both cases: thin and thick materials.

Better VISIBILITY of the scoring and cutting line.

Cast aluminium base, reinforced with central beam, for a greater STURDINESS.

Floating tables of galvanized steel. Improves STABILITY when cutting.

Swivel square, with central pivot. High PRECISION in angular cuts.

With lateral stop for repetitive or narrow cuts.

Equipped with 2 supplementary arms, to increase stability in large tiles.

Soft-grip handle for a better ERGONOMIC and COMFORT.

Includes 8 mm and 22 mm EXTREME scoring wheels. Compatible with all the RUBI PLUS scoring wheels range.

Includes carrying case.

Includes the new SLS (Secure Lock System), a more precise and efficient scoring system.

www.rubi.com



TECHNICAL SPECIFICATIONS

- Cutting length: 71 cm. (27")
- Maximum breaking power: 1200 kg. (2645 Lb)
- Maximum tile size in diagonal: 50x50 cm. (20x20")
- Maximum thickness: 3 - 21 mm w/o protector (1/8"-13/16") or 3 – 19 mm w/protector (1/8"-3/4").
- Weight: 13.3 kg. (29.32 Lb)
- Dimensions: 923x332x180 mm (36-11/32"x13-3/32"x7-3/32") (approx. with folded square).

www.rubi.com