



Ref.: 26965 (210/240V)

Ref.: 26995 (110/130V)

USE

Multipurpose electric mixer **WITHOUT CABLES**, to **BATTERY**, suitable for cementitious adhesives, resins, paint, and other materials.

Perfect for all those works where transportability, comfort and mixer manageability are essential factors.

FEATURED CHARACTERISTICS

PREMIUM quality electric mixer.

BRUSHLESS type motor with electronic control. Don't need maintenance and increase the product life.

Powered by Li-Ion 18V 5.0Ah battery.

ATTRACTIVE design, LIGHTWEIGHT & RESISTANT. Maximum RELIABILITY.

Ergonomic bi-material handle with improved grip that provides greater ERGONOMICS, COMFORT & STABILITY.

OTHER FUNCTIONAL CHARACTERISTICS

Equipped with 2 speed mechanical gearbox.

Progressive switch (rpm regulation) to OPTIMIZE the mixing of each material.

Anti-ignition SECURITY system. Prevents inadvertent start-up.

LED battery charge level indicator.

Mixing paddles connection through M14 thread continuous full rod and FAST-IN adapter.

Greater electrical SAFETY thanks to double isolation.

www.rubi.com



TECHNICAL SPECIFICATIONS

- Electrical power supply: Li-Ion 18V 5.0Ah battery (DC)
- Speed 1: 420 rpm / 13 Nm
- Speed 2: 700 rpm / 7.7 Nm
- Max. Mixing recommended capacity: 55 lbs (25 Kg)
- Ø Max. Mixing paddle: 120 mm.
- Connection thread: M14x30 mm female (normal step, 2 mm) for 19 mm key.
- IP mixer: 20
- Machine dimensions (assembled): 340x185x935 mm (with FAST-IN) / 340x185x905 mm (w/o FAST-IN).
- Work height: 840 mm. (with FAST-IN) / 810 mm. (w/o FAST-IN)
- Machine weight: 6.94 lbs (3.15 Kg) (with FAST-IN) / 6.52 lbs (2.96 Kg) (w/o FAST-IN)
- Carrying case weight: 8.26 lbs (3.75 Kg) (ref. 26155)
- Carrying case dimensions: 465 x 405 x 240 mm
- Mixing paddle weight (included): 1.87 lbs (0.85 Kg)
- Total product net weight: 18.95 lbs (8.6 Kg)

BATTERY:

- Battery ref. 26966: ENERGY BATTERY 18V 4AH
- Battery type: Li-Ion 5Ah
- Mixing autonomy: 90 l / 22 min (approx.)
- Charging time: 100 min. approx. (with 26967 3^a charger)
- Battery level indicator: Yes, through 4 colour LED (3 green + 1 yellow)
- IP battery: 20
- Battery weight: 1.65 lbs (0.75 Kg)

CHARGER:

- Voltage / Frequency: 210/240V 50-60HZ 3A (ref. **26965**)
110/130V 50-60HZ 3A (ref. **26995**)
- Insulation class: 2
- IP charger: 20
- Included adapters: In model **26965**: UK, AUS, EUR (ref. 26985)
In model **26995**: USA (ref. 26984)
- Weight: 0.94 lbs (0.43 Kg)

The RUBIMIX E-10 ENERGY includes:

- Energy battery 18V 5Ah.
- Energy charger 18V
- 3 helix mixing paddle Ø120 mm, removable, for mortar and cementitious adhesives.
- FAST-IN adapter.
- Carrying case and tools set.

www.rubi.com



PACKAGING

Carrying case with four-color cardboard band

Box dimensions: 42 x 31 x 26 cm.

Total weight: 9,7 Kg

Unit of sale: 1 unit.

NORM

Complies with the following European regulations:

EN 60745-1, EN ISO 12100, EN 55014-1, EN 55014-2, EN 61000-3-2, EN 61000-3-3, EN 62321.

According to derived regulations:

2006/42/EC, 2014/30/EC, 2012/19/EC, 2011/65/EC.

www.rubi.com