



Ref.: 50939

USE

Portable electric circular cutter. Suitable for dry or wet cutting.

For cutting all kinds of ceramic tiles Suitable for natural stone and sintered stone. Especially recommended for large tiles.

KEY FEATURES

PRACTICAL and EASY TO USE. ACCURATE cut thanks to the possibility of using a guided system.

Double cooling system, wet and dry. Greater adaptability to work environment.

Allows the user to reduce manipulation, handling heavy or awkward use.

Height-adjustable cutting head. FAST adjustment system.

OTHER FEATURES

Guiding mark for better visibility of the line of cut.

Switch with SAFETY lock. Prevents UNINTENTIONAL start-up. Electrical cable with PRCD.

Direct connection to vacuum cleaner. Includes adapter for other models or brands.

Equipped with lateral stop for parallel cuts.

Quick connection and regulating valve for hose** (16 mm diameter). Rubber cover for vacuum connection.

Includes TCR-180 SUPERPRO blade (dry cutting), transport case and accessories. FACILITATES transport and handling.

Suitable for discs with reinforcement plate, TVA type

www.rubi.com



TECHNICAL SPECIFICATIONS

- Power: 2.5 CV (P1: 1.8 kW).
- Voltage: 230V/50Hz with SCHUKO plug.
- RPM: 5800.
- Disc outer diameter: 180 mm. (The scales and graduations are determined for 180 mm discs).
- Disc inner diameter: 22.2 mm.
- Maximum cutting thickness: 55 mm.
- Net weight: 6.7 kg. (11 kg with case and accessories)
- Dimensions: 33x45x38 cm.
- Vibration value in accordance with UNE-EN 61029 is 1.7 m/s^2 , with an uncertainty of 1.5 m/s^2 .

PACKAGING

Neutral cardboard box.

Unitary box dimensions: 47x35.5x40 cm.

Sales unit: 1 unit.

Gross weight: 12 kg. (including case and accessories)

STANDARDS

EN 60745-1 EN 60745-2-1 EN55014-1 EN55014-2 EN61000-3-2 EN61000-3-11

It complies with the essential requirements of the following directives:

2006/42/EC 2006/95/EC 2004/108/EC 2002/96/EC 2011/65/EC

www.rubi.com