



Ref.: 50953*

* available in other voltages

USE

EXCLUSIVE accessory for users of SLIM CUTTER manual cutting system.

Portable electric circular cutter. Suitable for dry or wet cutting.

For cutting all kinds of ceramic tiles, ceramic sheet, natural stone and sintered stone. Especially suitable for large tiles.

KEY FEATURES

ACCURATE cut thanks to the SLIM SYSTEM guides.

Includes 2 SLIM suction pads to adapt TC-125 to SLIM CUTTER (versions older 2019).

Equipped with a carbon steel slide on adjustable stainless steel radial bearings.

Double dust reduction/control system. Dry & Wet cut.

Height-adjustable cutting head (saw effect), hinged from 0° to 45°. (mitre). FAST adjustment system.

BI-MATERIAL additional grip. Principally for mitre cuts.

OTHER FEATURES

Compatible with discs of 125 or 115 mm diameter. (Suitable for discs with reinforcement plate, TVA type).

Switch with SAFETY lock. Prevents UNINTENTIONAL start-up. Electrical cable with PRCD.

Direct connection to AS-30 PRO (32 mm diameter) vacuum cleaner. Includes adapter for other models and brands (37, 42 and 50 mm diameter).

www.rubi.com



OTHER FEATURES

Quick connection and regulating valve for hose** (16 mm diameter). Rubber stopper for suction outlet. IMPROVES ergonomics during wet cutting.

Cast aluminium disc protector with transparent polycarbonate cover with quick opening and closing system. FACILITATES disc change and MINIMISES the projection of particles and water.

Tilting side guard for mitre cuts. REDUCES water splashing and IMPROVES dust suction.

Includes TCR-125 SUPERPRO disc (dry cutting), transport case and accessories. FACILITATES transport and handling.

***Hose connector not included.*

TECHNICAL SPECIFICATIONS

- Power: 1.7 CV (P1: 1.25 kW).
- Voltages: 220-240V/50-60Hz with SCHUKO plug (ref. 50953).
 - 220-240V/50-60Hz with UK plug (ref. 51959).
 - 110-120V/50-60Hz with UK plug (ref. 51961).
 - 110-120V/50-60Hz with US plug (ref. 51957).
- RPM: 13800 (may vary depending on voltages and frequencies)
- Disc outer diameter: 115 / 125 mm. (The scales and graduations are determined for 125 mm discs).
- Disc inner diameter: 22.2 mm.
- Maximum cutting thickness: 20 mm (for 115 mm discs) and 25 mm (for 125 mm discs)
- Maximum mitre cutting thickness: 14 mm (for 115 mm discs) and 18 mm (for 125 mm discs)
- Net weight: 4.8 kg. (with standard disc)
- Dimensions: 330x239x206 mm.
- Vibration value in accordance with UNE-EN 61029 is 1.78 m/s², with a dispersion K=15.

PACKAGING

Four-colour printed cardboard box

Sales unit: 1 unit.

Gross weight: 7.1 kg.

STANDARDS

EN 60745-1:2009+A11:2010 EN 60745-2-22:2011+A1:2013 EN55014-1:2006/+A1:2009/+A2:2011

EN55014-2:1997/+A1:2001/+A2:2008 EN61000-3-2:2006/+A1:2009/+A2:2009 EN61000-3-3:2013

It complies with the essential requirements of the following directives:

2006/42/EC 2014/35/EU / 2014/30/EU / 2011/65/EC.

www.rubi.com