

**Ref.: 12955****Ref.: 12917 (INCH. VERSION)**

USE

Single guide manual tile cutter with multipoint breaker and swivel square for higher precision in angle cuts.

Ideal for INTENSIVE cut of any kind of ceramic tiles. Also ideal for porcelain stoneware (Bla/Ala).

KEY FEATURES

Steel rectangular guide of 12 mm thickness. High resistance to lateral bending.

RUBIFLEX handle for higher ERGONOMICS and COMFORT.

Laser engraved aluminium swivel square with central pivot. Higher PRECISION in angle cuts.

Operable with a single hand.

OTHER FEATURES

Assembly designed to be used by pulling the handle backwards.

MULTIPOINT breaker with foldable pressure pad (folds when scoring and unfolds when raise the handle).

Injected Aluminium base for a higher ROBUSTNESS.

With lateral stop for repetitive cuts and narrow strips.

Equipped with 1 supplementary arm for large ceramic tiles.

Includes Ø22 mm EXTREME scoring wheel. For ROUGH and SSTRUCTURED tiles. Also compatible with Ø22 mm scoring wheel (ref. 18914) for smooth surface tiles.

www.rubi.com



TECHNICAL SPECS

- Cutting length: 66 cm.
- Maximum BREAKING power: 1000 kg.
- Maximum diagonal size tile: 46x46 cm.
- Maximum cut thickness: 5 to 20 mm.
- Net weight: 11,5 kg.
- Dimensions: 936x336x225 mm. (aprox with folded square)

PACKAGING

Unitary cardboard box with RUBI's flexography

Unitary gross weight: 12,5 kg.

Unit of sale: 1 unit

Units per pallet: 12 units

Pallet dimensions: 120x100x105 cm.

Pallet weight: 172 kg.

www.rubi.com