



Ref.: 18948

USE

Compact electric thumping system specially designed for SLAB and large tiles.

Maximize the tile's moistening* and improves adhesion by removing air pockets between substrate and tile.

Indicated for use in tiled floors and walls.

**Don't use for long time on the same tile to prevent the adhesive from coming out.*

FEATURED CHARACTERISTICS

Compact and light design with only 4.8Kg weight, to facilitate vertical jobs.

Floating chassis with vibration reduction system for greater user comfort.

OTHER FUNCTIONAL CHARACTERISTICS

Contact board anti-marks. Easily exchangeable.

Easy to use tool with double ergonomic grip.

Vibration frequency not adjustable.

www.rubi.com



TECHNICAL SPECIFICATIONS

Voltage: 220-230v 50/60Hz

r.p.m.: 2940

Power: 0.03KW (0,04cv)

Protection: IP-65

Machine dimensions (mounted): 292 x 242 x 185mm

Weight: 4.8Kg (estimated 3D)

Cable lenght: 4.5m

Chassis: 1.5mm folded sheet steel in powder-coated with red finish

Vibration plate: Anti-mark PUR plastic easily exchangeable

Handle: Aluminium and plastic Soft-Grip type

PACKAGING

Machine dimensions (transport): 292 x 242 x 185mm

Unit of sale: 1 unit

NORM

European directives:

2006/42/CE Machinery directive

2014/35/UE Low voltage directive

2014/30/UE Electromagnetic compatibility directive

Derived regulations:

EN 62841-1:2016, EN ISO 12100:2012, EN 55014-1:2017, EN 55014-2:2015, EN 61000-3-2:2019,

EN 61000-3-3:2013/A1:2019