



Ref.: 45985

USE

Portable electric cutter.

Ideal for PROFESSIONAL cut of wall tiles and stoneware, or OCCASIONAL cut of porcelain and other stone materials.

Perfect for repairs and renovations. Machine suitable for indoor works.

FEATURED CHARACTERISTICS

Stainless steel table with a FOLDABLE side for mitering cuts. Adjustable for precise mitering cuts at 22.5 ° & 45 °

Extruded aluminium lateral stop. Securely adjusts and lock for maximum support on large format tiles. Simple action lever lock for fast, accurate repetitive cuts.

Guide for angle cuts that slides smoothly along the lateral stop, for diagonal cuts from 0 ° to 45 ° at left and right.

Transparent splash guard provides a clear view of the blade and line of cut for greater alignment precision.

OTHER FUNCTIONAL CHARACTERISTICS

DIRECT drive SINGLE PHASE motor with thermal protector.

WET cut. Blade cooling by IMMERSION.

Non-slip rubber feet for greater STABILITY.

www.rubi.com



Tubular steel chassis.

Fixed water tank with maximum level indication (1.6 L). Water recovery system by decantation system that allows reusing water and dirtying less.

Premium laser-cut 7in. diamond blade included for fast and smooth cuts with a long service life.

TECHNICAL SPECIFICATIONS

- Amperage: 4.8 A
- Voltage: 120 V / 60 Hz.
- P1 (kW): 0.58 kW
- RPM: 3450
- Max. cutting length: 20 in (508 mm)
- Max. tile format in diagonal: 13 in. (330 mm)
- Max. thickness: 1.25 in. (31 mm)
- Max. thickness when mitring: 0.78 in. (20 mm)
- Dimensions: 22.7 x 17.6 x 10.4 in (577 x 447 x 264.5 mm)
- Net weight: 21 lbs (10.5 kg)
- Cable length: 6 ft (1.8 m)

PACKAGING

Unitary full colour carton box.

Unitary box dimensions: 24.6 x 19.48 x 8,26 inch

Gross weight: 26.1 lbs

Units par pallet: 10 (EURO4)

15 (EURO5)

Pallet weight: 314,04 lbs (EURO4)

457,83 lbs (EURO5)

NORM

Meets de following standards:

CAN/CSA-C22.2 N° 71.2-10

USA / UL Std N° 987-8th Edition.

www.rubi.com