



Ref.: 45986

## USE

Portable electric cutter.

Ideal for PROFESSIONAL cut of wall tiles and stoneware, or OCCASIONAL cut of porcelain and other stone materials.

Perfect for repairs and renovations. Machine suitable for indoor works.

## FEATURED CHARACTERISTICS

Aluminium table with a FOLDABLE side for mitering cuts. Adjustable for precise mitering cuts at 22.5 ° & 45 °

Extruded aluminium 16" lateral stop. Securely adjusts and lock for maximum support on large format tiles. Simple action lever lock and automatic alignment for fast, accurate repetitive cuts.

High resistance aluminium guide for angle cuts that slides smoothly along the lateral stop, for diagonal cuts from 0 ° to 45 ° at left and right.

Transparent splash guard provides a clear view of the blade and line of cut for greater alignment precision.

## OTHER FUNCTIONAL CHARACTERISTICS

Anti-splash system that keeps dry the work area by reducing splash production.

Detachable table support. Allow straight cut up to 24" with the table support extended.

Convenient storage capacity that allows to store the blade's keys to save time and not lose them.

Integrated carry handle allows easy portability to work sites.

[www.rubi.com](http://www.rubi.com)



DIRECT drive SINGLE PHASE motor with thermal protector.

WET cut. Blade cooling by IMMERSION.

Tubular steel chassis and reinforced plastic supports.

Fixed water tank with minimum (1.5 L) & maximum (2 L) level indicator. Water recovery system by decantation system that allows reusing water and dirtying less.

PREMIUM diamond blade included for fast and smooth cuts with a long service life.

## TECHNICAL SPECIFICATIONS

- Amperage: 6.5 A
- Voltage: 120 V / 60 Hz.
- RPM: 3450
- Max. cutting length: 24 in (610 mm)
- Max. tile format in diagonal: 12 in (305 mm)
- Max. thickness: 1.25 in (31 mm)
- Max. thickness when mitring: 0.78 in. (20 mm)
- Dimensions: 23 x 19.75 x 10.5 in (584 x 501 x 267 mm)
- Net weight: 27 lbs (12.2 kg)
- Cable length: 6 ft (1.8 m)

## PACKAGING

Unitary full colour carton box.

Unitary box dimensions: 24,8 x 18,9 x 8,85 inch

Gross weight: 13,15 lbs

Units par pallet: 8 (EURO4)

12 (EURO5)

Pallet weight: 294,18 lbs (EURO4)

428,04 lbs (EURO5)

## NORM

Meets de following standards:

CAN/CSA-C22.2 N° 71.2-10

USA / UL Std N° 987-8th Edition.

[www.rubi.com](http://www.rubi.com)