



USE

Special blade for difficult and hard jobs.

For cutting all type of hard materials as granite, slate, natural stone, quartz conglomerate, rustic stoneware, clinker, refractory, and all kind of porcelain tiles.

The specific design of the diamond rim offers a higher cutting speed in the hardest materials without renouncing the finish quality.

High quality finish.

Dry cut (Ref. 30983 - Ø115)

Wet cut (Ref. 30984 - Ø200)

DIAMOND BLADE CHARACTERISTICS

Resistant blade type TURBO VIPER sintered.

Laser welding.

Steel body reinforced through welded plate.

Suitable for use with GRINDERS.

Warning:

DUE TO THE INCREASE OF BLADE BODY THICKNESS IN THE REINFORCED AREA, THE CUTTING LINE MAY BE DISPLACED FROM THE OWN GUIDE ELEMENTS OF THE TOOL USED.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height (cut): 10 mm.

Inner diameter: 22,2 mm.

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 30983 – Ø115: Rim thickness: 1,4 mm.

Maximum RPM: 13.300

Ref. 30984 – Ø200: Rim thickness: 2 mm.

Maximum RPM: 7.650

PACKAGING

Full-colour carton with anti-theft fixing clip.

Blister dimensions:

Ref. 30983 – Ø115: 17,5 x 15 mm.

Ref. 30984 – Ø200: 24,5x21 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com