

**Ref.: 26993****USE**

Portable electric cutter with plunge effect (Vertical cut).

Ideal for PROFESSIONAL cut of wall & floor ceramic tiles and other materials.

Perfect for repairs and renovations.

FEATURED CHARACTERISTICS

Incorporates tubular steel support and foldable, to transport the machine easily.

Universal motor with replaceable brushes.

With lateral stop for repetitive cuts with adjustment from 0 ° to 45 °.

Premium Laser-cut Blade: For fast, smooth cuts with long life.

OTHER FUNCTIONAL CHARACTERISTICS

Tilting cutting head adjusts for precise 22.5 ° and 45 ° bevel cuts.

Water tank with level indication min. and max.

Maximum capacity: 4.27 gal / 16.2 L

Aluminium main table. Rear water tray extensions in reinforced plastic.

TECHNICAL SPECIFICATIONS

- Amperage: 10 A
- Voltage: 120 V / 60 Hz
- P1 (kW): 1.10 kW
- RPM: 6000
- Max. cutting length: 24 in (609 mm)
- Max. tile format in diagonal: 18 in. (457 mm)
- Max. thickness: 2-1/4 in. (57 mm)
- Dimensions: 48 x 23.2 x 44.5 in (1220 x 590 x 1130 mm)
- Net weight DT: 47 lbs (21.35 kg)
- Net weight DT + support: 56.2 lbs (25.5 kg)
- Flanges: 1.81 in (46 mm)
- Diameter flanges shaft: 1.6mm / 1.2mm
- Arbour diameter: 16 mm.

PACKAGING

Carton box with RUBI flexography

Unitary box dimensions: 40.79 x 21.62 x 15.28 / 1036 x 549 x 388

Gross weight: -

Units par pallet: 1 (TBD)

NORM

Meets de following standards:

ETL US/Canada listed (meets or exceeds UL 987 standards)