



Ref.: 21979

USE

For small renovations and light jobs.

For the OCCASIONAL cut of glazed stoneware and FREQUENT of tile.

FUNCTIONAL FEATURES

STANDARD category.

Multipoint separator, with aluminum clamp.

Closed slides without bushings and aluminum tool holders.

Deep-drawn sheet steel base with central rib.

Injected aluminum guide supports, for greater ROBUSTNESS.

Double guide, for a better VISIBILITY of the scoring and cutting line.

Closed sliders made of POM.

Ø16 mm solid steel guides, chromed with anti-corrosion treatment.

Lateral stop made of sheet steel for repetitive cuts and square at 45°.

Scoring wheels adaptable to each material to obtain maximum performance and cutting quality in each case. Compatible with diameters from 6 to 10 mm.

Includes Ø6 mm scoring wheel.

www.rubi.com



TECHNICAL SPECIFICATIONS

- Cutting length: 61 cm.
- Maximum diagonal cut format: 43x43 cm.
- Maximum cutting thickness: 10 mm.
- Net weight: 4,875 kg.

PACKAGING

Four-color cardboard unit box.

Unit Box Dimensions: 770x155x105

Gross unit weight with packaging: 5.2 kg.

Sales unit: 6 units (in groupage box).

Groupage box dimensions: 800x325x345.

Groupage box gross weight: XXX

Units per pallet: 72 units (12 groupage boxes)

www.rubi.com