



Ref.: 03923

USE

For a precise and easy adjustment of the gap between tiles during floor or wall tiling.

FUNCTIONAL CHARACTERISTICS

PRO quality tile gap regulator.

Double suction cup system with vacuum pump with for secure fastening.

Large diameter suction cups (150 mm) for any kind of tile surface (flat, rough, structured, etc.)

For lateral displacement of tiles and gap reduction between 0 - 40 mm.

Enables to equal the level of the tiles between 0 - 20 mm.

Maximum lifting capacity up to 100 Kg (220 lbs).

THECNICAL SPECS

Material: Steel, plastic and rubber.

Dimensions: 480 x 150 x 120 mm

Net weight: 3.61 Kg

www.rubi.com



TILE GAP REGULATOR SRT

VERSION:

R-V.1.01

DATE:

APR 2021

PACKAGING

Sales unit: 1 unit / box

Unitary box dimensions: 480 x 160 x 120 mm (B1)

Unitary box total weight: 3.84 Kg

Units per pallet: 56

www.rubi.com

Is the customer's responsibility to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.