



Ref. 65970

USE

- For the tile installation joint applying.
- Available in different hardnesses according to the joint thickness.

FUNCTIONAL CHARACTERISTICS

- High resistant base sheet for a good sturdiness and lightness.
- The **SUPERPRO rubber grout float** (ref. 65970) includes a scratch resistant white rubber sheet, and offers a high flexibility, ideal for joints up to 3 mm thickness.
- The **TERMOFLEX SUPERPRO rubber grout float** (ref. 65976) is adaptable to any joint thickness due to its medium hardness. This rubber grout float stands out specially for its lightness.
- The **SUPERPRO solid rubber grout float** (ref. 65975) includes a high scratch resistant hard rubber plate. The hardness of this rubber plate makes this grout float suitable for joints above 3 mm thickness.
- All the rubber grout floats are suitable for all types of joint material.

TECHNICAL SPECIFICATIONS

- Plate material: ABS.
- Handle material: varnished beech wood.
- Rubber materials:
 - o Ref. 65970: body in EPDM y exterior plate in white rubber.
 - o Ref. 65976: body in TERMOFLEX y exterior plate in white rubber.
 - o Ref. 65975: scratch resistant hard rubber.
- Dimensions: 25x11x8 cm
- Net weight: 300 gr.

PACKAGING

- Sales units: 6 units.
- Group box dimensions: 36,5x26x9,7 cm.
- Group box weights:
 - o Ref. 65970: 2,18 kg
 - o Ref. 65976: 1,76 kg
 - o Ref. 65975: 3,9 kg