



USE

Professional manual cutter with high-performance MULTIPOINT breaker.

For INTENSIVE cutting of all types of ceramic tiles, ideal for porcelain tiles.

FUNCTIONAL CHARACTERISTICS

Breaker with forged aluminium pressure pad and sliders.

Equipped with radial double row bearings for smoother and more accurate sliding.

Closed cross-section extruded aluminium guides with chromed steel bearing raceway. Improves cutting accuracy.

Cast aluminium guide supports.

Includes the new SLS (Secure Lock System), a more precise and efficient scoring system.

Handle with soft grip for better ergonomics and comfort.

22 mm diameter, aluminium handle rod.

Steel frame. Greater robustness and durability. Increases the useful life of the breaker rib by minimising its wear.

Foldable table extensions with suspension system for large ceramic tiles.

www.rubi.com



Aluminium floating and foldable tables.

Rotating square with removable ends to aid transport. *Version available with square in inches (ref. 17958).

Rotating square locking system with knob. Higher locking force.

New 30 cm long lateral stop. Rotatable from 45° to 90° for repetitive cuts.

Good visibility of scoring.

Includes rubber wheels with handle and reinforced textile bag for transport.

Equipped with 8 mm and 18mm PLUS scoring wheels as standard.

TECHNICAL SPECIFICATIONS

- Length of cut: 155 cm.
- Maximum diagonal cutting size: 110x110 cm.
- Maximum cutting thickness: 21 mm.**
- Maximum breaking power: 1500 kg.
- Net weight: 31.5 kg.

** There are some ceramic materials thicker than 15 mm that, due to their physical characteristics, possible internal stresses or finishes, are difficult to cut manually. It is recommended to make sample cuts to determine the compatibility of the product.

PACKAGING

Dimensions of box: 191x28.1x26.7 cm.

Sales unit: 1 unit.

www.rubi.com