



15956 _ TK-850 –W/BAG

15957 _ TK-1020 – W/BAG

15958 _ TK-1300 – W/BAG

15959 _ TK-1600 – W/BAG

15976 _ TK-850 (33") – W/BAG

15977 _ TK-1020 (40") – W/BAG

15978 _ TK-1300 (51") – W/BAG

15979 _ TK-1600 (63") – W/BAG

Revolutionary cutter with formidable separation power and exceptional scoring visibility.

USE

- Professional manual cutter MONOGUIDE with high-performance MULTIPOINT breaker.
- For INTENSIVE cutting of all types of ceramic tiles, ideal for porcelain stoneware in sizes up to 1600 mm in length and 21 mm in thickness.

HIGHLIGHTS

- PREMIUM category.
- PURE POWER. 1500kg of maximum power combined with a mechanism with trigger system (under patent TX-MAX) that allows scratching and separating with one hand.
- ASYMMETRICAL GUIDE. PERFECT VISIBILITY OF THE SCORING WHEEL. Same visibility as RUBI double-guide cutters. (TZ patent).
- SWIVEL SQUARE WITH MAGNETIC FIXATION. Removable aluminum square, with a unique profile magnetic system for greater precision and to avoid any movement or misalignment. It also includes an additional screw fixation in order to completely fix the square profile.
- ROBUST AND FOLDABLE. The "chassis-guide" tandem gives the TK greater robustness and reduces the flexing of the assembly. The design of the machine in the folded position makes it easy to transport, both inside and outside the bag (folding tables under TZ patent).

OTHER FEATURES

- Equipped with radial bearings for smoother and more precise movement during the most demanding jobs.
- Steel chassis. Greater robustness and durability. Increases the life of the separating rib, minimizing wear on it.
- Extruded aluminum guide with closed profile with chrome steel raceway.
- Forged aluminum spacer and slides. The latter manufacturing process offers greater resistance to breakage in the slides.
- Cast aluminum guide brackets.
- "Soft-grip" handle for greater ergonomics and comfort.
- Side stop 30 cm long and swivel from 45° to 90° for repetitive cuts.
- Folding table supplements with suspension system for large format ceramics.
- Rubber wheels and handle for easy transport.
- Reinforced textile cover for easy transport. Greater protection and durability.
- Compatible with Secure Lock System (SLS) PLUS scoring wheels.
- Supplied with Ø8 SILVER PLUS and Ø22 EXTREME PLUS scoring wheels.

TECHNICAL SPECIFICATIONS

- Cutting length:
 - TK-850 – 85 cm (33")
 - TK-1020 – 102 cm (40")
 - TK-1300 – 130 cm (51")
 - TK-1600 – 160 cm (63")
- Maximum diagonal cut format:
 - TK-850 – 60 x 60 cm
 - TK-1020 – 70 x 70 cm
 - TK-1300 – 90 x 90 cm
 - TK-1600 – 110 x 110 cm
- Maximum cutting thickness**: 21 mm.
- Maximum separation power: 1500 kg.
- Net weight:
 - TK-850 – 41.8 lb (19 kg)
 - TK-1020 – 43 lb (19.5 kg)
 - TK-1300 – 54 lb (24.5 kg)

***There are some ceramic materials, with thicknesses greater than 15mm that, due to their physical characteristics, possible internal tensions or finishes, present difficulties to be cut manually. It is advisable to make some sample cuts to determine the compatibility of the product.*

PATENTS

- Patents linked to the TZ: Base and guides.
- Patents linked to the TX: separator system.

PACKAGING

- Gross weight:
 - TK-850 – 54 lb (24.5 kg)
 - TK-1020 – 57.32 lb (26 kg)
 - TK-1300 – 71.65 lb (32.5 kg)
 - TK-1600 – 74.95 lb (34 kg)
- Dimensions of the unit box:
 - TK-850 – 134 x 25 x 22 cm
 - TK-1020 – 151 x 25 x 22 cm
 - TK-1300 – 179 x 25 x 22 cm
 - TK-1600 – 209 x 25 x 22 cm
- Sales unit: 1 unit.