DRYGRES SUPERPRO

VERSION R-V.1

DATE OCT 2026



USE

- For dry drilling ceramic materials; wall tiles, glazed stoneware, porcelain stoneware and natural stone.

FUNCTIONAL CHARACTERISTICS

- SUPERPRO quality.
- Vacuum brazed diamond bit.
- For use with grinder.
- M14 thread connection for the global market and 5/8" thread connection for the US market.
- Dry cutting.
- Maximum working speed: 14,000 r.p.m.
- Maximum working thickness: 39 mm.
- Air cooling, by orbital movement.
- Those up to 12 mm in diameter incorporate a wax plug to improve the initial lubrication of the bit (first 4 - 5 perforations).
- For the US market, an adapter is offered to change the M14 thread to the 5/8" thread (ref. 05987).

RUBI TOOLS GROUP, S.A. Avda. Olimpiades 89-91 · 08191 Rubí (Barcelona) SPAIN · T. 34 936 806 500 · info@rubi.com · rubi.com

Is the customer's responsability to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropiate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.

- References available for global market (M14):

Reference	Diameter	Rpm max.	Maximum drilling thickness
05988	6 mm	14000	35 mm
05989	8 mm	14000	35 mm
05990	10 mm	14000	35 mm
05991	12 mm	14000	35 mm
04910	20 mm	14000	39 mm
57903	25 mm	14000	39 mm
04911	28 mm	14000	39 mm
04912	35 mm	14000	39 mm
04913	43 mm	14000	39 mm
04914	50 mm	14000	39 mm
04915	60 mm	14000	39 mm
04916	65 mm	14000	39 mm
04917	68 mm	14000	39 mm
05992	75 mm	14000	39 mm
57904	80 mm	14000	39 mm
57906	85 mm	14000	39 mm
57907	100 mm	14000	39 mm
57908	120 mm	14000	39 mm

RUBI TOOLS GROUP, S.A. Avda. Olimpiades 89-91 · 08191 Rubí (Barcelona) SPAIN · T. 34 936 806 500 · info@rubi.com · rubi.com

Is the customer's responsability to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropiate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.

- DRYGRES kits (50917) are composed of:

MULTIDRILL guide with carry case.
Dry cutting diamond drill bits:
Ø 1 1/8",1 3/8", 1 3/4" & 2 11/16"
(28 mm, 35 mm, 43 mm, 68 mm).
Case.

- DRYGRES kits (50936) are composed of:

MULTIDRILL guide with carry case
Dry cutting diamond drill bits:
Ø 1 1/8", 1 3/8", 1 3/4", 2" & 2 11/16"
(28 mm, 35 mm, 43 mm, 50 mm, 68 mm).
Case.

- DRYGRES kits (50996) are composed of:

MULTIDRILL guide with carry case
Dry cutting diamond drill bits:
Ø 1/4", 5/16", 3/4", 1 3/8", 50 & 2 11/16"
(6 mm, 8 mm, 20 mm, 35 mm, 68 mm).
Case.

- KIT MINI DRYGRES (50938) is composed of:

Dry cutting diamond drill bits:
Ø 1/4", 5/16", 3/8" and 1/2"
(6 mm, 8 mm, 10 mm, 12 mm).
Case.

- KIT TCR BLADE AND DRYGRES DRILL BITS (68923) are composed of:

Dry diamond cutting disc TCR – 115
Four dry cutting diamond drill bits:
Ø 2 x 1/4", 13/16", 1 3/8"
(2 x 6 mm, 20 mm, 35 mm).
Case.

RUBI TOOLS GROUP, S.A. Avda. Olimpiades 89-91 · 08191 Rubí (Barcelona) SPAIN · T. 34 936 806 500 · info@rubi.com · rubi.com

Is the customer's responsability to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropiate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.

- References available for the US market (5/8"):

Reference	Diameter	Rpm max.	Maximum drilling thickness
5993	1/4" (6 mm)	14000	35 mm
5902	1-1/8" (28 mm)	14000	39 mm
5987	1-3/8" (35 mm)	1400	39 mm
5903	2" (50 mm)	14000	39 mm
5934	25/32" (20 mm)	14000	39 mm
5936	1-11/16" (43 mm)	14000	39 mm
5937	2-9/16" (65 mm)	14000	39 mm
5938	2-61/64" (75 mm)	14000	39 mm
5996	DRYGRES KIT		

- DRYGRES KIT (5/8") for USA (05996) are composed of:

MULTIDRILL guide.
Dry cutting diamond drill bits Ø 1 1/8", 1 3/8", 1 3/4", 2" & 2 11/16" (28 mm, 35 mm, 43 mm, 50 mm, 68 mm).
Case.

PACKAGING

- Cylindrical transparent PVC blister with process label.
- Dimensions:
  - Ø 6 a 28 mm: 3.4x3.4x12.5 cm.
  - Ø 35 mm: 4,3x4,3x12,8 cm.
  - Ø 43 mm: 5,2x5,2x13,1 cm.
  - Ø 50 a 65 mm: 7,4x7,4x13,6 cm.
  - Ø 68 a 75 mm: 8.5x8.5x14 cm.
  - Ø 80 a 120 mm: 13.8x13.8x8.6 cm.
- 1 unit per blister.
- Warning for ref. 05988/05989/05990/05991 and for 05993/05932/05901: Store at temperatures below 80ºC.

RUBI TOOLS GROUP, S.A. Avda. Olimpiades 89-91 · 08191 Rubí (Barcelona) SPAIN · T. 34 936 806 500 · info@rubi.com · rubi.com

Is the customer's responsability to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropiate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.