



Ref.: 52825
52826 (USA)

USE

- Accessory for mini angle grinders specifically designed to perform high-quality **45°** mitre cuts along the edge of tiles, in both dry and wet cutting applications.
- It is particularly recommended for porcelain tiles up to 20 mm thick, and any stone material of unlimited length.

MAIN FEATURES

- Suitable for both dry and wet mitre cutting applications.
- "Zero Dust" working environment thanks to an adjustable dust extraction unit, that can be connected to a vacuum cleaner to capture almost all dust generated during dry cutting. During wet cutting, it also helps collect a significant proportion of the water and slurry produced.
- Adjustable minimum gap setting. The blade position can be finely adjusted,
- Two operating modes:
 - Sliding the tool along the tile edge, without length limitation.
 - Sliding the tile across the unit, with the tool attached to any version of the SLAB Table. This setup is particularly suitable for repetitive dry cuts on smaller tiles. An additional support accessory is included to facilitate tile entry and improve stability at the start of the cut.
- Outstanding finish quality and easy handling thanks to a dual-bearing blade support system that minimises vibration, delivering cleaner, more precise cuts.

OTHER FEATURES

- SUPERPRO category accessory for PROFESSIONAL use.
- Compatible with most angle grinders on the market (Ø115 mm to Ø125 mm). Suitable for both corded and cordless models, featuring a secure and straightforward attachment system based on a threaded spindle and quick-release fastening strap.
- Ergonomic handle design that provides excellent control, particularly at the start of the cut.
- Standard threaded hole to attach the angle grinder handle for better control and easier sliding on the tiles.
- Removable blade guard ensures quick and effortless blade replacement.
- Includes TVR-125 SUPERPRO diamond blade.
- Grinder Anchor Types: M14 or 5/8"-11.
- Easy and quick to transport and install.
- Spanner included for quick and convenient assembly and blade changes.

TECHNICAL SPECIFICATIONS

- Dimensions (closed): 460 x 250 x 205 mm (18 x 10 x 8")
- Dimensions (open): 460 x 260 x 205 mm (18 x 10 x 8")
- Net weight: 4 kg (aprox) (8.8 lb)
- Cutting length: No limitation
- Cutting Capacity 45° Mitre Cuts:
 - o Ø125 mm blade: up to 20 mm
 - o Ø115 mm blade: up to 15 mm
- Bevel regulation: Progressive roughing adjustable in 10mm
- Chassis: Aluminum and Carbon steel
- Sliding skates: White Polyethylene Plastic (PE-1000 UHMW) with high friction resistance.
- Blade protection: Sheet metal
- Compatible grinder: Mini grinders with cable or battery (not included)
Up to Ø125mm (recommended 850w max)
- Grinder fixation: M14 (EU) - 5/8 (USA) shaft and quick closing belt

COMPATIBLE AND COMPLEMENTARY PRODUCTS

- 52949 ANGLE TECH ENERGY CAS (W/O BAT-CHARGER)
- 52963 ANGLE TECH USA ENERGY CAS (W/O BAT-CHAR)
- 18935 MESA SLAB

- 18984 MESA SLAB VERSA-TILE
- 50962 ASPIRADOR AS-30 PRO 230V 50/60HZ
- Additional RUBI diamond blades for specific materials and cutting requirements.
- All SLAB range.

PACKAGING

- Unit box dimensions: 49.6 x 27.1 x 21.8 cm (19.5 x 10.6 x 8.5")
- Unit box gross weight: 4.7 kg (10.3 lb)

REGULATIONS

No certification CE needed. Accessory only.