

Ref.: 53097

USE

- Accessory for dry and wet cutting of large-format tiles with the TC-125 G2. It allows cuts to be made without the need for guides.
- It also allows for 45° cuts; it is recommended to make these on the edge of the tile.

MAIN FEATURES

- SUPERPRO category accessory for OCCASIONAL use with the TC-125 G2 tile cutter.
- Allows for both manually guided cuts (freehand) and edge-guided cuts using the side stop, for any tile format without minimum or maximum size limitations.
- Enables miter cuts with the TC-125 G2, as well as other special cuts such as center cuts or recessed cuts.
- Easy to assemble: Quick and easy assembly to the TC-125 G2 using a fixing system consisting of an aluminum guide that allows for smooth bearing movement and quick locking with a knob.

OTHER FEATURES

- Easy and intuitive to use, taking full advantage of the TC-125 G2's features.
- Graduated side stop for improved guidance and a better finish on the cut. Allows for repetitive cuts without having to measure each time. Essential for miter cuts on the tile edge.
- The maximum strip that can be cut in a straight line using the side stop is 15 cm. Beyond this width, the accessory is used without the stop, allowing for free cutting.

GERMANS BOADA S.A. Pol. Can Rosés · Avda. Olimpiades 89-91, P.O.BOX 14 · 08191 RUBI (Barcelona) SPAIN · T. 34 936 80 65 00 · gboada@rubi.com

Los datos, informaciones y recomendaciones contenidos en esta ficha técnica, referentes a productos, forma de empleo y aplicaciones, se basan en los conocimientos actuales · Los valores específicos pueden sufrir variaciones, ya que quedan fuera de nuestro control a causa de las diferentes condiciones que puedan presentarse en el uso y aplicación de nuestros productos · Es responsabilidad del cliente asegurarse, mediante sus propios ensayos y pruebas que cada producto satisface el propósito al que se destina y si las condiciones reales se utilización son las más adecuadas · Los datos y la propia ficha técnica pueden ser modificados sin previo aviso.

- Allows you to adjust the margin left from the original tile edge when making miters, thus increasing the operator's control over the cut finish.
- Includes a carrying case.

TECHNICAL SPECIFICATIONS

- Dimensions (with side stop and knobs): 438 x 260 x 74 mm
- Net weight: 1.50 kg

CUTTING CAPACITY

-Straight: Ø125 Blade: 20 mm

- Miter: Ø125 Blade: 13 mm

- Maximum cutting distance with side stop: 150 mm

Compatible accessory with:

- 51951 TC-125 G2 230V 50/60 HZ
- 51967 TC-125 G2 230V 50/60 HZ UK
- 51977 TC-125 G2 120V 50/60HZ USA
- 51987 TC-125 G2 110V 50/60 HZ UK
- 52952 TC-125 G2 230V 50/60 HZ SRT

PACKAGING

- Suitcase with full-color printing strap.

- Groupage of 7 units.

NORMATIVES

N/A

GERMANS BOADA S.A. Pol. Can Rosés • Avda. Olimpiades 89-91, P.O.BOX 14 • 08191 RUBI (Barcelona) SPAIN • T. 34 936 80 65 00 • gboada@rubi.com

Los datos, informaciones y recomendaciones contenidos en esta ficha técnica, referentes a productos, forma de empleo y aplicaciones, se basan en los conocimientos actuales • Los valores específicos pueden sufrir variaciones, ya que quedan fuera de nuestro control a causa de las diferentes condiciones que puedan presentarse en el uso y aplicación de nuestros productos • Es responsabilidad del cliente asegurarse, mediante sus propios ensayos y pruebas que cada producto satisface el propósito al que se destina y si las condiciones reales se utilización son las más adecuadas • Los datos y la propia ficha técnica pueden ser modificados sin previo aviso.